



SPURBMIP

Design by Dima Loginoff

Collection consisting of aluminium ceiling lamps and suspended lamps.

Available in several colours and sizes.


Typology: SUSPENSION LAMP

Ratings

- •Built in LED module
- •Supply voltage: 220-240 Vac
- •CCT 2700K, 3000K* or 3500K
- •IP20
- •Surface installation over holes
- •Dimmable PHASE CUT
- •Aluminum body painted
- •Diffuser opalescent

SP URBMI P

kg 0,5 m³ 0,004



Product code composition

IIDRAN / DRIVER INCLLIDED

URBAN / DRIVER INCLUDED						
Туре	Article	ССТ	CODE	Colours	LED Source	
SP	URBMI P	1 2700K	х	BC wrinkled white	LCC 6.5 W - diffused beam	
		2 3000K*		BR matt bronze		
		3 3500K		NI matt nickel		
	'	'	'	•	'	



220-240V_{AC} **LED** ~671 lm* 103 lm/W*

example composition code SP URBMI P 1 X NI LCC

Available colors







BR Matt bronze



NI Matt nickel

CUSTOMER

NOTES

SPURBMI P_X __LCC

NOTICE: Luminous flux (Im) and efficacy (Im/W) for all LED luminaires is based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.