

WIREFLOW

Design by Arik Levy.

VIBIA

Reference

0320.

Application

Hanging lamps

Installation type

Surface / Built-in

Description

Wireflow designed by Arik Levy. Linear hanging lamp. Its appearance, as a structure of fine cables finished with two 4,5W LED terminals, is ideal for discretely connecting with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements. Ideal for decorating large spaces, particularly ones with high ceilings, including hotel reception areas, retail sales points and food and drinks bars.

Diffuser

Polycarbonate diffuser

Materials


Body: Aluminum
Horizontal rods: Steel
Ceiling rose: Aluminum

Finish



0320-04 Black (RAL 9005)


Sketch



Electrical characteristics

2 x LED 4,5W 350mA

Total 9.0 W



Light source: 2700K CRI >80 981 lm 109 lm/W

Fixture: 453 lm 50.33 lm/W

Driver included: CC - Constant Current 350 mA 110-240V 50/60Hz

Electronic dimming: 1-10V Push

ficha.fichatecnicaproducto.regulacion.opcional DALI

Technical characteristics

- Linear canopy

Physical characteristics

1 Box / 0.08 x 0.20 x 0.70 m. / Vol. 0.0105 m³ /

Gross weight 3.1 kg. / Net weight 2.6 kg.


Installation and assembly

Please, see the installation manual

Light distribution

Highlight

Lamp used to highlight a specific element.



Photometric data

Efficiency : 46.23%

Coordinate system : CG

Total flux : 980.60

Maximum value : 320.25

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m



Certificates

