PANZERI

Zero Square

24V DC M03201.050.0410

Data sheet

CODE	M03201.050.0410
SYSTEM POWER CONSUMPTION	25W
EFFICACY	81.56lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	2835lm
LUMEN OUTPUT	2039lm
EFFICIENCY	71.9%
WEIGHT	0,92 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS (CM)	58,0 x 58,0 x 10,0




Single or multiple suspension lighting fixture for interiors, with direct and indirect light emission. $% \left({{{\left[{{{\rm{s}}_{\rm{c}}} \right]}_{\rm{c}}}_{\rm{c}}} \right)_{\rm{c}}} \right)$

Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.


Extruded polycarbonate diffuser with opaline finish. Suspension kit with griplocks and 5m (196,9") long steel cables. 5m (196,9") long power cable in transparent PVC. Provided without power canopy.



Technical drawing



Polar diagram



______ _____C0 - C180 - - - C90 - C270



