PANZERI

Venexia

220-240V AC ON-OFF

EL04819.022.0201





Data sheet

CODE	EL04819.022.0201	
SYSTEM POWER CONSUMPTION	8W	
EFFICACY	74.25lm/W	
LIGHT SOURCE	LED	
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h	
COLOUR TEMPERATURE	2700K Ra>80	
LIGHT DISTRIBUTION	diffused	
POWER SUPPLY	220-240V AC	
FREQUENCY	50/60Hz	
ELECTRICAL CONFIGURATION	ON-OFF	
DRIVER	integrated included	
NOMINAL LUMINOUS FLUX	930lm	
LUMEN OUTPUT	594lm	
EFFICIENCY	63.9%	
WEIGHT	3,40 Kg	
PROTECTION DEGREE	IP65	
COLOUR TOLLERANCES	SDCM 3	
SHOCK RESISTANCE RATING	IK06	
PACKING DIMENSIONS	27,0 x 35,0 x 22,0 cm	



Suspension lighting fixture for indoor or outdoor spaces, with direct light emission. Turned aluminium structure in corten, mat brass or micaceous grey polyacrylic paint.

Transparent silicone gaskets.

Screen in partially mat cast glass.

Aluminium closing disk in polyacrylic paint.

Nickelled brass M12 cable gland.

Stainless steel screws.

2m (78,7") long suspension and power cable in neoprene.

Power canopy with galvanized sheet metal ceiling bracket and die-cast aluminium $\,$ covering in corten, mat brass or micaceous grey polyacrylic paint.











Technical drawing



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270