



SP LIAP 1I
Design by Sara Moroni

Collection consisting of metal suspended lamps.
Available in several colours and sizes.
Built-in dimmable LED light source.

Typology: suspended

Ratings


- Built in **LED** module
- CCT 3000 K
- optic ~40° beam
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Dimmable 0/1-10V

SP LIA P 1I (RECESSED)

Product code composition

kg 1,5 m³ 0,0591

LIAISON / DRIVER NOT INCLUDED



Type	Article	Arch / Final & sphere finishes	Led source
SP	LIA P 1I	NE black / NE black	LED 6,6W - optic ~ 40° beam 3000K* 2700K upon request
		NE black / OO matt gold	
		OO matt gold / NE black	

Compatible with pivot system
pag.76

IP20 CRI>90 LED 700mA - 9,4Vdc ~671 lm* ~102 lm/W*
example composition code SP LIA P 1I NE NE LED

Available colors



NE/NE
Black/black

OO/NE
Matt gold
/black

NE/OO
Black/ Matt
gold

Customizable

SPLIAP1I _ _ _ _ LED

CUSTOMER _____ NOTES _____

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.